EXC-P40AP2 LED Pixel Light



Application Environment：
Indoor
Outdoor

Description

EXC-P40AP2 full-color series consists of professional chip LED pixel lights specially designed by EXC for outdoor high-rise landscape lighting. Each pixel is a separate lighting pixel, and each pixel can realize 65536 grades gray scale changing; they can be used for extra-large area display of building facades, contour shaping, interior and exterior surface decoration lighting; the pixel pitch can be customized; its installation is simple and reliable.

Features

- The newest generation technology: DMX512 parallel bus design
- Integrated clip-on endless connection
- Fully sealed and waterproof design with high thermal conductive adhesive imported from Germany
- Special outdoor lightning and ESD protection


Basic Specifications

Color	RGB+W
Working Voltage	24V
Max. Power Consumption	1.8W
Light Source	4pcs SMD RGB+ 2pcs SMD W LEDs
CRI	80
Control	DMX512
Grey Scale	8bit, 16bit
Source Life	50,000h
RDM	Optional
LED chip Brand	Optional(Cree, OSRAM, Lumileds, Epistar, etc...)
Cover	PC(Transparent,Opal)
Housing	PC+ABS
Weight	35g
Dimensions	62mm x 40.5mm x 15mm (L x W x H, exclude Mounting Bracket)
Installation	Installation with profiles
Working Temperature	-40°C to 50°C

Storage Temperature	-40°C to 70°C
Protection Rating	IP66
Luminous Flux	25LM/W(RGB), 50LM/W(White), 30LM/W(RGBW)
Central Light Intensity	21cd
Beam Angle	120°


Light Intensity Distribution

Light Intensity Chart




Physical Dimension

Unit：mm



Installation By Aluminum Profile




System connection diagram：

1、Host controller should connect with slave controller. Working voltage for controllers are AC220V.


2、On-line main controller should connect with slave controller, on-line main controller and sub controller working voltage are AC220V.

3、 each sub-controller with 8 ports, with each port 512 pixels, supporting data converter, supports 100 meters ultra-long haul transmission.

4、The CAT-5 e. cable distance should be within 100 meters between host controller and slave controller, between slave controllers and switch, etc.




Offline Controlling System Diagram




Accessories :

1: Female and Male Connector(Connect to first dot light for signal transmission)



2: Y Shape Connector(For power Distribution)



3: Interconnection Cable(1.3M,3M,5M is standard length)



4: End Cap

