







NOTES:

ELECTRICAL:

1. VOLTAGE RATING :125V AC RMS
2. CURRENT RATING :1.5A mp
3. CONTACT RESISTANCE :100 MILLI OHMS MAX
4. INSULATION RESISTANCE :1000M OHMS MIN@ 500V DC
5. DIELECTRIC STRENGTH :750V AC RMS 60Hz,1MIN
6. CAT.6A PERMANENT LINK: CONFORM TO ANSI/TIA/EIA-568 B.2-1
   ISO/IEC 11801:2002 CLASS EA

ENVIRONMENTAL:

1. Stotage :-40° TO+70°
2. Operation :-10° TO+60°

MECHANICAL

1. SHIELD MATERIAL BRASS C2680 T=0.25MM
2. HOUSING MATERIAL PC UL94V0
3. CONTACT MATERIAL PHOSHOR BRONZE PLATING GOLD
4. RJ45 JACK LIFE:750 TIMES MIN
5. RETENTIVENESS OF INSERTION STRUCTURE :50N 60±5S

RoHS 2.0 and REACH COMPLAINT

MATERIAL LIST:

NO.	PARTS NAME	SPECIFICATION STANDARD	QT'Y	REMARK
②	RJ45 JACK	Housing-fireproof PC Pin-8P8C 3u″ gold plated		
①	PCB	1.2mm		

CUSTOMER	CL-KJ-C5A07		
PRODUCT NAME			

REV.	BY	REVISION RECORD MODIFICATIONS	DATE
A	WANG	NEW	

DRAWNBY	CHECKBY	APPOBY	DATE
WANG	LI		