HOTEC

AUTOMATIC SANITARY WARE

Automatic sensor faucet (adjustable) ITEM: 19.115







COMPONENTS & MATERIALS

·Touchless sensor faucet, surface mounted.
·Adjustable the hot and cold water.
·Highest durability and rusting resistance.
·Easy install and maintenance.
·Suitable for hotel bathrooms.
·Saving water.

TECHNICAL SPECIFICATIONS

·Made of AISI 304 stainless steel, chrome finish.
·DC/AC
·Powered with 4 "AA" batteries of 1,5 V. Life: 1 year.
(based on 200 cycles one day.)
·Suitable water pressure: 0.05-0.6 MPa
·Ambient temperature: 0-45 ℃
·Ambient humidity: ＜95%RH
·Dia.of inlet pipe: G1/2" (DN15)
·Dia.of outlet pipe: G1/2" (DN15)
·Degree of protection by enclosure: IP56
·Detection zone: 6-25cm. Preset 15 cm. The date based on 30x30 cm standard white board.
·Equipped with fixing materials.

TECHNICAL SPECIFICATIONS

Power: DC/AC
Suitable water pressure 0.05-0.6 MPa
Degree of protection by enclosure IP56



Tel: +86 571 888 685 70 Fax: +86 571 888 685 71
hotec@cnhotec.com www.cnhotec.com