HOTEC

HAND DRYER

SENSOR OPERATED	EXCEL



Reference: 11.281
steel
white enamelled coating



Reference: 11.282
AISI 304 stainless steel
brigh



Reference: 11.283
AISI 304 stainless steel
satin

COMPONENTS & MATERIALS

·One-piece cover.
·High speed brush motor.
·Strong, vandal proof and build without edges.
·Universal brush motor incorporating a safety thermal cut-off.
·Electronic infrared detection sensor.
·Aluminium centrifugal single inlet fan wheel.
·Easy maintenance.
·Dimension: 325 high x 295 wide x 171 deep mm.

TECHNICAL SPECIFICATIONS

· **Material**	steel or AISI 304 stainless steel
· **Cover thickness**	1.0 mm thick
· **Voltage/Frequency**	AC220V, 50/60Hz
· **r.p.m.**	20000
· **Total power**	1800W
· **Motor power**	650W
· Consumption	7.8A
· **Air velocity**	85m/s
· **Air temperature**	50-80℃
· **Noice level**	<78dB
· **Protection level**	IPX1

CERTIFICATE

CE RoHS

TECHNICAL DRAWING



Tel: +86 571 888 685 70 Fax: +86 571 888 685 71
hotec@cnhotec.com www.cnhotec.com